

CONCRETE SECURITY SCREWS

Bryce Fastener's hardened alloy steel Concrete Security Screws are meant to be used in a pre-drilled 3/16 hole. They effectively secure assets in block, brick, and concrete.

BryKote™ must be added to these security fasteners for corrosion protection. Our Concrete Security Fasteners are automatically made with an oversized Raptor™ Security Head. This permits the extreme torque required to drive the fastener and provides a better hold. Raptor™ Security Heads do not need washers or lock washers.

Applications for these Specialty Security Screws include:
Protecting repossessed properties, security fencing, security doors, and security protection for vacated properties affected by hurricanes.

\$100.00 minimum for STYKFIT®7 Security Drive.
2,500-piece minimum for Key-Rex® Security Drive.



▲ 1/4 x 2 STYKFIT®7
Concrete SMS Security Screw,
Alloy Coated with BryKote™

Available in These Security Screw Drives & Head Styles:



Key-Rex®
2,500-Piece Min.



STYKFIT®7
\$100 Min.





RAPTOR™ BHCS



RAPTOR™ FHCS

Raptor™ Head Replaces Washer

Which Security Screw Drive Do I Need?

Raptor™ Head Concrete Security Screws									
Basic Screw Diameter	Hi- Low Thread	Raptor™ Head Diameter		Raptor™ Head Height		2" Thread Max	Lengths Available (INCH")	Key-Rex®	STYKFIT®7
		MAX	MIN	MAX	MIN				
.250	1/4"	.525	.498	.145	.130	2"	1" – 3"	X30	Y30
								Elite-Security Level	High-Security Level
								Exclusive-to-You Security Drive	Fast-Driving/ High-Torque/ 7-Lobes
								Minimums Vary	\$100 Minimum
								2,500, 1,200, or 500-piece min	



Made in USA
Engineered & Crafted
100% in the USA