

A BRYCE
EXCLUSIVE



MADE FROM
316 STAINLESS
STEEL



Made in USA
Engineered & Crafted
100% in the USA

SECURITY CONCRETE ANCHORS

Strong Just Got Stronger.

LOOKING FOR A SECURITY CONCRETE ANCHOR?

Bryce's **Penta-Nut™** and **Key-Rex® Nut** act as security saviors when paired with concrete studs or sleeve anchors.

We recommend using **Penta-Nut™** for an easy, economical solution when security is needed in a concrete application. Penta-Nut™ easily replaces the regular nut and washer used in these anchors.

The Penta-Nut Fastener diameter is the width of a washer and eliminates the need for it. They can also be used with studs that have been epoxied into the concrete. Aluminum or specialty railings and public art displays are two applications where replacing the standard nut with a Penta-Nut™ secures assets from theft or tampering.

Made from **316 Stainless Steel** with \$100.00 minimums

We don't stock sleeves or studs but can supply them if needed.

Our Special Order **Key-Rex® Nut** is recommended when you need an **Elite-Security Level** where the nuts and sockets have **Exclusive-to-You Drives**. Minimums vary from 2,500, 1,200 to 500 pieces depending on size.



▲ **Penta-Nut™** – The world's largest diameter Security Nut available, and with the Raptor Claw Option, needs no washer. This High-Security 316 Stainless Steel Nut turns any bolt into a lock.



SPECIAL
ORDER

▲ **Key-Rex® Nut** – The world's most secure, Tamper-Proof Security Nut on the market. Every set is custom "keyed" for the client, so only the client has the sockets that fit their custom set, which are designed to be nearly impossible to remove without the socket.

**A BRYCE
EXCLUSIVE**




**MADE FROM
316 STAINLESS
STEEL**



Made in USA
Engineered & Crafted
100% in the USA

SECURITY CONCRETE ANCHORS



Basic Screw Diameter	Thread Pitch Course	Nut Diameter	Key-Rex® Nut Driver	Penta-Nut™ Driver
.250	1/4 – 20	.660"	1GRNS50	1GPNS25
.3125	5/16 – 18	.83"	1GRNS55	1GPNS31
.3125	5/16 – 18 LARGE DIA	1.00"	1GRNS62	1GPNS37
.375	3/8 – 16	1.00"	1GRNS62	1GPNS37
.50	1/2 – 13	1.25"	1GRNS75	1GPNS50
.50	1/2 – 13 LARGE DIA	1.375"	N/A	1GPNS60
.625	5/8 – 11	1.375"	N/A	1GPNS60
.625	5/8 – 11 LARGE DIA	2.0"	N/A	1GPNS60
.75	3/4 – 10	2.0"	N/A	1GPNS87
.87	7/8 – 9	2.0"	N/A	1GPNS87
1.00	1 – 8	2.0"	N/A	1GPNS910
— METRIC WITH INCH TRANSLATION —				
Reference	Thread Pitch Course	Nut Diameter	Key-Rex® Nut Driver	Penta-Nut™ Driver
.236"	M6 x 1.0	16.7mm (.660")	1GRNS50	1GPNS25
.315"	M8 x 1.25	21.1mm (.83")	1GRNS55	1GPNS31
.394"	M10 x 1.5	25.4mm (1.00")	1GRNS62	1GPNS37
.472"	M12 x 1.75	31.7mm (1.25")	1GRNS75	1GPNS50
.551"	M14 x 1.5	34.9mm (1.375")	N/A	1GPNS60
.630"	M16 x 2.0	50.8mm (2.0")	N/A	1GPNS87
.787"	M20 x 2.5	50.8mm (2.0")	N/A	1GPNS87
.87"	M22 x 2.5	50.8mm (2.0")	N/A	1GPNS87
.944"	M24 x 3.0	50.8mm (2.0")	N/A	1GPNS910

- Large Diameter Penta-Nut™ Holds Higher Loads.
- Penta-Nut™ is Stock.
- Key-Rex® is Special Order Only.